

Research for Detection Level and Production Sales Management of Raisins Based on NN and SAS/GIS

^{1,2}Li Xiaoling and ³Yuan Jimin

¹School of Computer Science and Technology, Chengdu University,

²Key Laboratory of Pattern Recognition and Intelligent information Processing, University, Chengdu 610106, P.R. China

³School of Computer Science and Technology, Panzhihua University, Pan Zhihua 610106, P.R. China

Abstract: Raisins grade identification in China still relies on photoelectric sorting and manual separation, also, the function of management system for the production, processing, and sales of raisin is traditional and simple. This study presents a processing method on the basis of the Neural Network (NN) and image manipulation. Calculating the length of the long-short-axis, marking the location of it and calculated the 7 parameters, chroma, length, width and etc, and using boundary tracking algorithm, A BP NN was to build and identify the level of raisins through analysis of the external characteristics of raisins. The result of experiment indicates that average recognition rate is higher than 92%. This study took regional economy statistics of Pan Zhihua as an example, designed a system based on regional economy statistic and achieves the analytic function of regional economic statistics by utilizing distributed SAS /GIS to release the data, provide browsing, searching and analytic function of the space data for the users and accomplish data share. Therefore, the method has a great practical value, which can be applied to other.

Keywords: Image manipulation, neural network, raisin detection, SAS/GIS

INTRODUCTION

The usefulness of image detection technology to identify agricultural research has been extensively researched and applied (Tang *et al.*, 2007). The fruit quality detection and classification is applied wildly (Xie *et al.*, 2010). Some new ways with computer technology and image processing to test the quality and surface (Bao *et al.*, 2004).

At present, there are photoelectric sorting and manual separation with regard to distinguish the grading of raisins. Method of Manual separation is based mainly upon human observation to determine the level (Wang and Gao, 2004). And the other is based primarily on color characteristics, utilizing surface testing to determine level of raisins by the equipment automatically (Diep, 2007). These two methods have many disadvantages in the applications.

The analysis and management for agricultural product are very important to improve the quality of products and manage the data of the characteristics. The SAS System and SAS/GIS software allow us to perform many different kinds of analysis and data management functions, as well as produce many different types of text-based and graphical presentation output. Many types of data have a spatial aspect, including demographics, marketing surveys, customer addresses,

and epidemiological studies. As the further application of GIS and the fast development of object-oriented programming and the component technology, the spatial management function easily achieves the analysis and application of the regional economy.

In this study, image processing and analysis technology are combined with artificial neural networks to identify and grade raisins. The secondary development module and visual programming language are used to develop the analytic system of regional economy, realize common data management, graphic processing functions etc., strengthen statistic analysis and optimize the functions of spatial and location analysis. One of the key ways is image manipulation algorithms and characteristic testing, linked to artificial neural networks through extracting valid characteristic parameter. Another of the key way is used SAS and GIS.

CHARACTERISTICS PARAMETER HIS MODEL

First the photos of raisins can be got and be expressed by 640×480 pixel, 24-bit true color BMP, as shown in Fig. 1. In order to identify and grade raisins, the characteristics of a single raisin need extracting. The following focus on extraction method of color,



Fig. 1: Raisin image (The left: First-grade raisin image; the right: Second-grade raisin image)

shape, and other characteristics. Here it needs to give a HIS model to represent the parameters of the raisins characteristics. HSI model is defined as follows:

$$I = (R + G + B) / 3 \quad (1)$$

$$S = 1 - \frac{3}{(R + G + B)} [\min(R + G + B)] \quad (2)$$

$$H = \arccos\left\{ \frac{[(R - G) + (R - B)] / 2}{[(R - G)^2 + (R - B)(G - B)]^{1/2}} \right\} \quad (3)$$

(if $B \leq G$)

$$H = 360^\circ - \arccos\left\{ \frac{[(R - G) + (R - B)] / 2}{[(R - G)^2 + (R - B)(G - B)]^{1/2}} \right\} \quad (4)$$

(otherwise $B > G$)

The mean value of H, S, I are shown as Eq. (5)-(7):

$$\bar{H} = \frac{1}{n} \sum_{i=1}^n H_i \quad (5)$$

$$\bar{S} = \frac{1}{n} \sum_{i=1}^n S_i \quad (6)$$

$$\bar{I} = \frac{1}{n} \sum_{i=1}^n I_i \quad (7)$$

where,

\bar{H} = The mean value of tones

\bar{S} = The mean value of saturation

\bar{I} = Illumination value

Image manipulation: The images need pre-treating for extracting characteristic data and get the parameters of RGB in the HSI model. The image pre-treatment including image denoising, background, segmentation, boundary tracking and raisin extraction. Making the background white, non-background part of the original image is retained, and Set the corresponding pixel of the original image to 255. The colored image of raisins can be indicated as R (red), G (green) and B (blue). (Zhang and Liu, 2004) Based on the When segmenting the background of color images, the researcher first




Fig. 2: Results of background segmentation in three channels (The left: Segmentation in R channel; the middle: Segmentation in G channel; the right: Segmentation in B channel)

Table 1: Average of raisin features

Grade	H	S	I	A
First	44.6560	0.4831	0.3365	140.2411
Second	36.1369	0.4516	0.3586	102.6020
Third	32.1393	0.5245	0.4018	67.4189

conducted threshold as far as the gray image concerned, and then compared the original color image with treated image. If pixel is 255 (having treated image, the Eq. (8)), and the threshold is shown as follows:

$$c_n(i, j) = \begin{cases} c_{n_0}(i, j) & c_{n_0}(i, j) \leq T_m \\ 255 & c_{n_0}(i, j) > T_m \end{cases} \quad (8)$$

Here $n = 1, 2, 3$, and $m = 1, 2, 3$. When $n = 1, 2, 3$, it respectively stands for $R(i, j), G(i, j), B(i, j)$. $c_{n_0}(i, j)$ respectively stands for $R_0(i, j), G_0(i, j), B_0(i, j)$ when $n = 1, 2, 3$. $R(i, j), G(i, j), B(i, j)$ are gray value of three-channel pixel before and after the background segmenting. T_m , respectively stands for T_r, T_g, T_b when $m = 1, 2, 3$. T_r, T_g, T_b are the threshold of segmenting background for three channels R, G and B. The parameter of Area shape is shown as Eq. (9):

$$A = \frac{1}{2} \sum_{i=1}^{N_b} [x_i y_{i+1} - x_{i+1} y_i] \quad (9)$$

where,

N_b = The numbers of the boundary

The result of segmenting is shown in Fig. 2.

Selection and Extraction of characteristics parameter. According to the area feature in the Green theorem, calculate three levels (each contain 60) of raisin samples, and get mean score of 7 characteristics, identify the parameters color, saturation, brightness, long, area, length and width as a means of identification features. Part parameters are shown as Table 1.

RAISIN GRADE-LEVEL UNDER BP NETWORK CHECKUP

The structure of BP NN: The relation between the form feature and grading is comparatively complex which is hard to distinguish one from another. So we make use of BP NN to establish the relationship between form feature and grading which is helpful to distinguish the different grades. The NN structure has 7

Table 2: Recognition rate of different parameters

	Parameter number							Epoch of learning	Recognition rate (%)
	H	S	I	P	A	L	M		
7	√	√	√	√	√	√	√	976	93
6	√	√		√	√	√	√	973	91
5	√			√	√	√	√	1181	93
5		√		√	√	√	√	9302	88
4	√			√		√	√	1961	93
4	√			√	√	√		1183	90
4	√			√	√		√	930	91
4	√				√	√	√	907	92

inputs, 3 outputs and an implied layer. The input has 7 corresponding feature parameters, while the output is corresponding with the 3 grades of the raisin. The initial study velocity is 0.01. Self study velocity is adopted. The target error is 0.0005. The 240 samples are made up of 60 raisins in 4 different grades, respectively. Identifiable samples are 120 raisins with 40 raisins of each grading.

The results of recognition: Recognition rate of different parameters are shown as the Table 2. From Table 2, hroma, area, length, width is relatively important parameters. At the same time, these 4 features are more efficient than those 7 features. So the cyber structure adopts the system with 7 inputs, 3 outputs and a middle layer with 17 nerve cells.

Database design and main function of system: In order to manage the data about products of the raisins, a system be programming based on SAS/GIS. The system provides the modules of management of regional economy data, spatial query, calculation of statistic analysis, graphic analysis chart, space etc.

System developing platform and structure: According to the thought of system expansibility and the need of SAS system, this system uses the systematical structure of C/S. Database uses relation database, SQL Server 2000 and stores spatial data, business data, metadata etc. Logic application layer consists of bottom data layer, middle Public application components and upper application components. Bottom database engine of spatial data (Super map SDX) and data source management database engine components (ADO.NET) compose the bottom data layer. The upper application components include thematic application components and GIS application components (Super map components). Components accomplish the mutual use through COM interface. Implementation level achieves the user's dynamic interactions and various functions of the system through user interface (GUI) (Xie, 2004). Detailed structure is illustrated in Chart1. GIS exploring platform selects component object platform, (Component GIS) Super Map Objects 5.0 (Xiao *et al.*, 2008).

System module based on SAS/GIS: SAS/GIS software uses two basic types of data which are spatial

data and attribute data (Wang *et al.*, 2004). The spatial data describes the location, shape, and interrelationships of map features and represent point features, line features and area features of map. To represent point, line, and area features in the map, the attribute data provide information that relates to the map features. Attribute data are all other data that are related to map features in some way, including the data to analyze in the context of the map. Also attribute data can be stored in the spatial database (Jones *et al.*, 2003).

- **Statistic data management of raisins:** Statistic data includes categories of products, quality, sales etc. Because of a huge mass of statistic data, regional enterprise economy statistic data and spatial data are respectively input and stored. At first, input economy statistic data to a sequential document edit and store in the relevant file of database.
- **Modules of spatial query and statistic analysis:** Spatial query includes buffer query, crossing query, and interaction query of chart data and attribute data etc (Lan *et al.*, 2003). The system supports the statistical function and finishes the statistical function of data of raisins product. For instance, those statistic information, such as total number, mean, standard deviation etc. At the same time, the system carries out the functions of spatial statistic analysis and reflects the spatial connection of economic development. These statistical data showing on the geographic base helps to make a correct decision about the development tendency for the raisins products in the whole region.
- **Geographic analysis module:** According to different requirements, diverse charts express economy data of every administrative region. It usually adopts pie chart, point density diagram, histogram, line chart etc. Drawing the graphs of the same region at different periods visually reveals the law of regional economy development. Parts of codes are as following:

```
public SLThematicMap(Panel chartContainer,
ObservableCollection<ObservableCollection<object>>
table)
{this.chartContainer = chartContainer;
```



Fig. 3: The statistics result

```

        this.table = table;
    } #endregion
    #region
    Dictionary<string, DataSeries> dicDataSeries =
new Dictionary<string, DataSeries>();
    DataSeries GetDataSeries(string sTitle)
    {if (!dicDataSeries. ContainsKey(sTitle))
    {
        RenderAs renderAsEnum; // out parameter
        dicDataSeries. Add(sTitle, new DataSeries()
{RenderAs
Enum.TryParse<RenderAs>(ChartRenderAs, true, out
renderAsEnum) ? renderAsEnum : RenderAs.Column,
XValueType
ChartValueTypes.Auto,
Name = sTitle,
LegendText = sTitle,
//YValueFormatString = "#",
ShowInLegend = ChartShowInLegend,
});
}
return dicDataSeries[sTitle];
}
    
```

CONCLUSION

Separating raisins is based on image manipulation technology, through the border tracking algorithms. The research put forward to a new method which uses the BP network to identify the level of raisins. The result of experiment indicates that the calculating method and judging of the level of raisins are precise and accurate, with an average recognition rate of 93%.The statistic result of the SAS/GIS system is illustrated in Fig. 3. At

present, this system has applied statistics for management and got a good result.

REFERENCES

Bao, X., R. Zhang and L. Zhong, 2004. Apple grade identification method based on artificial neural network and image processing. *Trans. CSAE*, 20: 109-112.

Diep, M.M., 2007. Analysis of deployed software. *Proceeding of the 6th Joint Meeting on European Software Engineering Conference and the ACM Sigsoft Symposium on the Foundations of Software Engineering: Companion Papers*, pp: 595-598.

Jones, C.B., A.I. Abdelmoty and G. Fu, 2003. Maintaining onto logies for geographical information retrieval on the web on the move to meaningful internet systems. *Lect. Notes Comput. Sc.*, 288: 934-951.

Lan, H.X., F. Wu and C. Zhou, 2003. Spatial hazard analysis and prediction on rainfall: Induced landslide using GIS. *Chinese Sci. Bull.*, 48: 703-708.

Tang, J.L., X. Jing and D.J. He, 2007. Research of classification of raisin basedon BP networks. *J. Agri. Mech. Res.*, 23: 51-53.

Wang, J.Y., G.G. Miao and Y. Cheng, 2004. The data acquisition of spatial information system. *Hydrographic Surv. Charting*, 24: 1-4.

Wang, Y. and H. Gao, 2004. Study on the segmentation and orientation of fruit image under natural environment. *Comput. Eng.*, 30: 128-129, 162.

Xiao, G.R., P.G. Cheng and H.Y. Pan, 2008. The design and implementation of regional economic statistics analysis system based on GIS. *Sci. Surv. Mapp.*, 33: 182-184.

Xie, F.Y., 2004. On photoelectric technology of colour sorting for Raisin. *J. Hunan Agri. Univ., Nat. Sci.*, 30: 71-73.

Xie, Z.H., X.Q. Guo and C.Y. Ji, 2010. A method of color fruit image segmentation based on the color model and the texture feature. *Comput. Eng. Sci.*, 32: 64-66, 100.

Zhang, R.Y. and S.S. Liu, 2004. Researches and applications of computer vision technique in fruit and vegetables commercialization after harvesting. *J. Yuzhou Univ., Nat. Sci. Edn.*, 21: 497-501.