

## Effect of Weight and Draught on the Performance of Disc Plough on Sandy-loam Soil

<sup>1</sup>O.M. Olatunji and <sup>2</sup>R. M. Davies

<sup>1</sup>Department of Agricultural and Environmental Engineering,  
Rivers State University of Science and Technology, P.M.B. 5080,  
Port Harcourt, Rivers State, Nigeria

<sup>2</sup>Department of Agricultural and Environmental Engineering,  
Niger Delta University, Wilberforce Island, Bayelsa State

---

**Abstract:** In this research, the relationship between depth of cut, increase in weight of disc plough as well as the draught has been investigated using dimensional analysis on a sandy loam soil. The experiment was conducted on a site with three different moisture contents level at five different speeds (0.83, 1.39, 1.94, 2.5 and 2.78 ms<sup>-1</sup>). It was observed that the depth of penetration increase with an increase in draught and increase in soil moisture content. From the site, the depth of cut was minimum at 4.9% and maximum at 9.4% moisture content. The result obtained from the validation shows that the model can be used effectively to determine the depth of cut in sandy loam soil and also the draught-speed relationship obtained from this work can be used to predict the power requirement of the disc plough in other soil types. The draught increase linearly with the depth of cut as predicted from the model. The result of the soil properties after tillage showed increase with shear strength, bulk density and depth.

**Keyword:** Disc plough, sandy - loam, moisture content, shear strength, bulk density, depth

---

### INTRODUCTION

Soil tillage may be defined as the mechanical manipulation of the soil aimed at improving soil conditions for crop production. It represents the most costly single item in the budget of an arable farmer. Tillage provides good weed control with low herbicide cost; allows the control of disease and insects by destroying them through burying of crop residues. Three things are involved in soil tillage which include: The power source, the soil and the implement (Olatunji, 2007).

The draught requirement of the disc plough is very enormous when compared to other tillage implements (ASAE, 2002). For a given soil type and speed of travel, Sheruddin (1992) and Grisso *et al.* (1996) observed that the disc plough has a higher total and specific draught than other tillage implements. This is attributed to the design of the implement. A similar result was observed by Singh and Pederson (1979) on the comparison of mould board and disc plough on Bangkok Clay. However, the two implements were tested at different moisture content levels. In an experiment conducted by Summer *et al.* (1986), it was observed that the draught was linear with speed for chisel, discs and sweep ploughs and had a quadratic relationship with speed for mould board ploughs. Linearity was observed between draught and depth for all the tools. The author also discovers the soil properties that contribute to tillage energy. They are moisture content, bulk density, soil texture and strength.

The typical draught requirements depend on the soil texture; implement width, working depth and travel speed ASAE (1999), McGreery and Claude (1984) examined the effect of disc angle in penetration and die draught of disc plough and noted that a considerable bearing area of the disc is in contact with soil, resulting in soil pressure on the back of the cutting edge. They explained that increase in disc angle and reduction in tilt angle improves penetration under hard soil conditions. Furthermore, they stated that depth of penetration of the disc blade during ploughing depends on the weight of the implement. Sheruddin *et al.* (1992), Kaul and Egbo (1985) reported that different speeds affect the soil aggregation as higher percentage of small soil aggregates were obtained at lower forward speeds than higher forward speeds. Claude (1984) reported that the weight on the disc is the most important factor affecting the depth of penetration of the disc.

Therefore, the objectives of this work are:

- To investigate the effect of weight of disc plough on the depth of penetration during ploughing
- To investigate the effects of soil moisture content and tool speed on draught energy requirement for disc ploughs.
- To develop an equation for predicting the depth of cut of disc plough at a given weight of the implement.



**MATERIALS AND METHODS**

The field test was carried out at NCAM, Ilorin, Nigeria which is 370 m above sea level and lies on longitude 40°30' East and latitude 8°26' North with mean annual rainfall and air temperature of 1000 mm and 30°C, respectively. The instruments used in the research work were: Two 75Hp Diesel Tractor, (Elcher 485 DI). A three bottom disc plough (63 cm diameter per disc), ranging poles, surveyor tape, stop watch, core soil sampler, soil samples containers, set of sieves, weighing balance, polythene bags, electric oven, desiccators, measuring cylinder, calibrated wooden bar and meter square frame.

**Experimental procedure:** All laboratory and field test carried out were done according to the recommendation of the Regional Network for Agricultural Machinery (RNAM, 1983). The experiment was conducted in a rectangular plot measuring 100m x 50m each and performance parameters studied were soil inversion, soil aggregation; depth and width of cut and fuel consumption at three different forward speeds. Two tractors A and B were made available. The implement (disc plough) was mounted on tractor B and made to plough the field following the field operational pattern for five consecutive runs during which the measured data were obtained.

A hydraulic dynamometer (pull type) was attached to the front of tractor B. Another auxiliary tractor A was used to pull the implement mounted tractor through the dynamometer. The auxiliary tractor pulled the implement mounted tractor in neutral gear but with the implement in the operating position (RNAM, 1983). The draught was recorded within the measured distance of 50 m as well as the time taken to reverse it. On the same field, the implement was lifted out of the ground and the rear tractor was pulled to record the idle draught force. The difference gave the draught of the implement. Additional weight of 10kg was added to the weight of the plough and the experiment repeated.

The depth of cut was measured with a steel tape from the bottom of the furrow to the surface level of the soil at seven randomly selected places for each of different weight of the disc plow from the test plot. (RNAM, 1983). A model was developed using dimensional analysis to analyse the experimental result. The model equation from dimensional analysis was validated by using the standard error of estimate (Murray and Larry, 2003).

**Model derivation and validation:**

**Model Derivation:** In the ploughing process the depth of cut depends on the weight of the implement, draught, cone index, moisture content and the speed. The depth of cut is the dependent variable which must be controlled by manipulating the other variables.

Let n be the number of variable involved in this operations, then n = 5 in this case. Similarly, let k be the fundamental dimensions which is *MLT*, then k = 3, therefore, the number of Pi-term equals 2.

The variables are:

Depth of Cut,	<i>d</i>
Weight of the implement,	<i>W</i>
Draught,	<i>D</i>
Cone Index	<i>CI</i>
Moisture content,	$\phi$
Speed of Operation,	<i>V</i>

Following methods of dimensional analysis by Olatunji (2007), the reference dimensions are M, L, T, (Mass, Length and Time, respectively).

$$\begin{aligned} \text{i.e., } d &= L \\ W &= M \\ D &= MLT^{-2} \\ CI &= ML^{-2} \\ V &= LT^{-1} \end{aligned}$$

$\phi$  = (Dimension less) hence  $\phi$  becomes a pie term. Therefore,

$$\phi = \pi_1 \dots \dots \dots 1$$

Since *d* is the dependent variable

$$d = f(W, D, CI, \phi, V) \dots \dots \dots 2$$

But since  $\phi$  is dimensionless and is a pie term Eq. 2 becomes:

$$f(d, W, D, CI, V) = 0 \dots \dots \dots 3$$

Let the repeating variables be W, CI and V:

$$\begin{aligned} \pi_2 &= W^{x_2} CI^{y_2} \times V^{z_2} \times d \dots \dots \dots 4 \\ MLT &= M^{x_2} \times (ML^{-2})^{y_2} \times (LT^{-1})^{z_2} \times L \dots \dots \dots 5 \text{ For} \\ M, \quad x_2 + y_2 &= 0 \dots \dots \dots 6 \\ L, \quad -2y_2 + z_2 + 1 &= 0 \dots \dots \dots 7 \\ T, \quad -z_2 &= 0 \dots \dots \dots 8 \end{aligned}$$

From the Eq. 6, 7 and 8 above

$$\begin{aligned} z_2 &= 0, \\ y_2 &= \frac{1}{2} \text{ and } , \\ x_2 &= -\frac{1}{2} \end{aligned}$$

Substituting the value of x, y and z, Eq. 4 becomes

$$\begin{aligned} \pi_2 &= W^{-1/2} \times CI^{1/2} \times d \dots \dots \dots 9 \\ \pi_2 &= \sqrt{\frac{CI}{W}} \times d \dots \dots \dots 10 \\ \pi_2 &= d \times CI^{1/2} \times W^{-1/2} \dots \dots \dots 11 \end{aligned}$$



To complete the 3rd pie term

$$\pi_3 = W_3^x \times CI_3^y \times V_3^z \times D \dots\dots\dots 12$$

$$MLT = M_3^x \times (ML^{-2})_3^y \times (LT^{-1})_3^z \times (MLT^2) \dots\dots\dots 13$$

For,

$$M, \quad X_3 + y_3 + 1 = 0 \dots\dots\dots 14$$

$$L, \quad -2y_3 + z_3 + 1 = 0 \dots\dots\dots 15$$

$$T, \quad -z_3 - 2 = 0 \dots\dots\dots 16$$

From the equations:

$$Z_3 = -2$$

$$Y_3 = -\frac{1}{2} \text{ and}$$

$$X_3 = -\frac{1}{2}$$

Substituting the value of  $x_3$ ,  $y_3$  and  $z_3$  Eq. 12 gives

$$\pi_3 = \frac{D}{\sqrt{W} \times \sqrt{CI} \times V^2} \dots\dots\dots 17$$

$$\pi_3 = D \times W^{-1/2} \times CI^{-1/2} \times V^{-2} \dots\dots\dots 18$$

But,

$$\emptyset = \pi_1$$

Therefore substituting all the pie terms into the functional equation we have

$$f(\pi_1, \pi_2, \pi_3) = 0 \dots\dots\dots 19$$

$$f(\emptyset, d \times CI^{1/2} \times W^{-1/2}, D \times W^{-1/2} \times CI^{1/2} \times V^{-2}) = 0 \dots\dots\dots 20$$

$$d \times CI^{1/2} \times W^{-1/2} = f(\emptyset, D \times W^{-1/2} \times CI^{1/2} \times V^{-2}) \dots\dots\dots 21$$

The equation above is the functional relationship between the dependent and the independent variables.

To get  $d$ , a new pie group can be determined from the existing pie groups by combining  $\pi_2$ , and  $\pi_3$ ,

$$\pi_2 = \pi_2 \times \pi_3 \dots\dots\dots 22$$

$$\frac{D}{\sqrt{W} \times \sqrt{CI} \times V^2} \times \frac{\sqrt{CI}}{\sqrt{W}} \times d \dots\dots\dots 23$$

$$\pi_2 = \frac{D \times d}{W \times V} \dots\dots\dots 24$$

$$f(\pi_1, \pi_2) = 0 \dots\dots\dots 25$$

$$\frac{D \times d}{W \times V} = k\Phi \dots\dots\dots 26$$

shown combining results.  
Therefore,

$$d = \frac{k \emptyset WV}{D} \dots\dots\dots 27$$

K is a constant and can be determined experimentally.

k value for sandy loam soil is 6.7, for soft soil is 5.7 and for firm soil is 7.8 (ASAE 2002).

**Data Collection and Analysis:** Data were collected as described above. The model equation from dimensional analysis was used to compute the values of depth of cut from the field data obtained.

The computed result was validated using

$$\pi_1 = \frac{D \times d}{W \times V} \dots\dots\dots 28$$

$$f(\pi_1, \pi_2) = 0 \dots\dots\dots 29$$

$$\frac{D \times d}{W \times V} = k\Phi \dots\dots\dots 30$$

Therefore,

$$d = \frac{k \emptyset WV}{D} \dots\dots\dots 31$$

K is a constant and can be determined experimentally.

k value for sandy loam soil is 6.7, for soft soil is 5.7 and for firm soil is 7.8 (ASAE 2002).

**Data Collection and Analysis:** Data were collected as described above. The model equation from dimensional analysis was used to compute the values of depth of cut from the field data obtained. The computed result was validated using the standard error of estimate. Also, analysis of variance was carried out to determine the effect of soil moisture and tool speed on the drawbar pull of the tractor.

## RESULTS AND DISCUSSION

**Effect of soil moisture and tool speed on soil strength properties:** Tables 1 and 2 show the average soil properties determined before and after tillage operation, respectively. The shear strength and cone index decreased with increased speed and soil moisture content but decreased with depth of cut. This shows that the draught force changes with depth of cut. These results corroborate with the findings of Singh and Perderson (1979), Thomas and Sing (2002).

**Effect of speed and moisture on draught and depth of cut:** The changes in draught with respect to speed and soil moisture content are shown in Tables 3 a, b and c.



Table 1. Average soil properties before tillage

SubPlot	Depth (CM)	Moisture Content %	Shear Strenght T	Cone index N/M <sup>2</sup>	Bulk Density Y (g/cm <sup>3</sup> )
1	7	3.47	30.17	60.66	1.30
	14	4.00	38.32	83.32	1.42
	21	3.77	49.12	49.12	1.48
2	7	5.29	22.41	45.66	1.23
	14	5.55	43.00	86.78	1.26
	21	5.70	45.42	103.56	1.29
3	7	8.75	20.32	32.76	1.22
	14	7.66	42.64	62.13	1.31
	21	7.59	53.57	38.24	1.35

Table 2 Average soil properties after tillage

SubPlot	Depth (CM)	Moisture Content %	Shear Strenght T	Cone index N/M <sup>2</sup>	Bulk Density Y (g/cm <sup>3</sup> )
1	7	3.71	15.45	12.06	1.26
	14	4.22	21.40	34.67	1.38
	21	4.03	32.67	86.43	1.39
2	7	5.28	19.20	42.72	1.42
	14	5.54	42.10	81.40	1.17
	21	5.52	37.00	101.57	1.20
3	7	7.14	21.50	8.42	1.09
	14	6.85	23.50	30.10	1.24
	21	7.03	37.24	63.21	1.29

Table 3. Effect of Speed and Soil Moisture Content on Draught and Power Requirement of Disc Plough

Moisture Level %	Speed of Ploughing (M/S)	Draught (KN)	Specific Draught (KN/M <sup>2</sup> )	Power Requirement (KW)
4.9	0.83	3.19	19.9	2.65
	1.39	3.27	20.4	4.55
	1.94	5.20	32.5	10.10
	2.50	6.25	39.1	15.63
	2.78	6.58	41.1	18.29
5.7	0.83	3.78	23.6	3.14
	1.39	4.23	26.4	5.88
	1.94	5.47	34.2	10.61
	2.50	6.94	43.4	17.35
	2.78	7.35	45.9	20.43
9.4	0.83	2.76	17.35	2.29
	1.39	3.65	22.8	5.07
	1.94	5.45	34.1	10.57
	2.50	7.34	45.9	18.35
	2.78	7.45	46.6	20.71

From the model derived, draught for disc ploughing increased with speed and soil moisture content (4.9, 5.7 and 9.4%), respectively. However, at the three soil moisture level, 4.9, 5.7. and 9.4% the draught and power requirement increased with speed. But draught requirement was lowest at soil moisture 9.4% and ploughing speed of 0.83 m s<sup>-1</sup> compared to soil moisture 4.9 and 5.7% at 0.83 m s<sup>-1</sup> This is because higher moisture content of the soil, hence the plough require less energy to carry out its function.

A comparative analysis of Tables 3 a, b and c shows that a tool speed of 1.94 m s<sup>-1</sup> gives a better performance in the area of depth of cut and draught required than the speed of 1.34 and 2.5 m s<sup>-1</sup>, respectively. This point to the fact that optimum speed of operation for disc ploughing is 1.94 m s<sup>-1</sup> while the optimum soil moisture content is between 8.0 and 9.4% for the soil under consideration. From the model derived the observed trend in Table 3a,b, and c can be explained by the fact that at higher soil

Table 5. Measure computed depth of cut and weight of implement at various speeds.

a. Speed of ploughing at 0.83 m s<sup>-1</sup>

Replication	Measured Depth Cut (cm)	Computed Depth Cut (cm)	Weight (kg)
1	8.12	9.00	450.00
2	8.32	8.90	460.00
3	8.97	9.23	470.00
4	9.10	9.45	480.00
5	9.62	9.87	490.00
6	10.30	10.20	500.00
7	10.04	10.04	510.00
8	10.87	11.21	520.00
9	11.32	11.01	530.00
10	11.89	12.00	540.00

b. Speed of ploughing at 1.39 m s<sup>-1</sup>

Replication	Measured Depth Cut (cm)	Computed Depth Cut (cm)	Weight (kg)
1	11.46	13.00	450.00
2	11.95	13.31	460.00
3	12.78	13.60	470.00
4	13.28	13.89	480.00
5	13.79	14.18	490.00
6	14.57	14.47	500.00
7	14.76	14.76	510.00
8	14.87	15.05	520.00
9	15.39	15.34	530.00
10	15.45	15.62	540.00

c. Speed of ploughing at 1.94 m s<sup>-1</sup>

Replication	Measured Depth Cut (cm)	Computed Depth Cut (cm)	Weight (kg)
1	13.96	14.41	450.00
2	14.37	14.90	460.00
3	14.90	15.12	470.00
4	15.22	15.56	480.00
5	15.78	16.00	490.00
6	16.42	16.78	500.00
7	17.00	17.25	510.00
8	17.99	17.90	520.00
9	18.00	18.04	530.00
10	19.45	19.00	540.00

d. Speed of ploughing at 2.50 m/s

Replication	Measured Depth Cut (cm)	Computed Depth Cut (cm)	Weight (kg)
1	27.02	29.01	450.00
2	27.87	29.68	460.00
3	28.69	30.32	470.00
4	29.68	31.00	480.00
5	31.11	31.61	490.00
6	31.89	32.26	500.00
7	32.67	33.00	510.00
8	33.63	33.55	520.00
9	34.16	34.19	530.00
10	35.35	34.84	540.00

e. Speed of ploughing at 2.78 m s<sup>-1</sup>

Replication	Measured Depth Cut (cm)	Computed Depth Cut (cm)	Weight (kg)
1	13.80	14.00	450.00
2	14.10	14.52	460.00
3	14.98	15.10	470.00
4	15.21	15.43	480.00
5	15.97	16.11	490.00
6	16.70	16.36	500.00
7	16.84	16.97	510.00
8	17.42	17.42	520.00
9	17.90	18.00	530.00
10	18.23	18.88	540.00



moisture contents, the degree of shearing and shattering of clods is reduced leading to a lower impact force Thomas and Singh, (2002). This further corroborates the findings of Singh and Pedersen (1979), Manian *et al.* (2000) that when moisture contents exceed the plastic limit value, the draught per unit area decreases. The draught increased linearly with the depth of cut as predicted from the model. The draught speed relationship can be used to estimate the tractor horse power required to pull the tillage implement for a given ground speed and operating depth. Table 4 shows the result of ANOVA on the effect of soil moisture content and tool speed on draught. The ploughing speed and soil moisture content had no significant effect on draught. The interaction between the ploughing speed and soil moisture content was not significant.

**The effect of weight on the depth of cut:** The results from Tables 5 a-e, as predicted from the model show that the depth of cut varied with a change in the weight of the implement. Also from the model, an increase in the weight of the implement at a constant speed, showed an appreciable increase in the depth of cut. This is in agreement with the findings of Singh and Pedersen (1979).

From the model at speed, 1.39 and 2.5 m/s it was discovered that the ploughing efficiency was lower compared with the speed of 1.94 m/s. At 1.94 m/s speed, with added weights the implement was able to penetrate deeper to the soil which help to remove some buried root and hard pan in the soil.

## CONCLUSION

The field work was carried out to investigate the effect of weight and draught on the performance of disc plough on sandy loam soil. The model validation and analysis of variance on the data collected showed that the draught for disc plough increase with speed and soil moisture content also the depth of cut varied with a change in the weight of the implement. An increase constant speed showed an appreciable increase in the depth of cut of ploughing. This is in agreement with the findings of Singh and Pedersen (1979), Summer (1986) The analysis further revealed that at tool speed of 7 km h<sup>-1</sup> and soil moisture levels 5.7% d.b and 9.6 d.b, the drawbar pull required to produced a good soil till was minimal. The application of the model derived will aid planning in tillage operations.

## REFERENCES

ASAE 1999. Data ASAE D 230.3. Agricultural Machinery Management Data. Agricultural Engineering. Year Book 1982, St. Joseph MI 49085.

- ASAE Standards 2002. Terminology and Definitions for Soil Tillage and Soil-Tool Relationships. ASAE, Ep 291.1, pp: 192-194.
- Claude Culpine, C., 1984. Farm Machinery. 10th Edn. Granada Publishing Ltd-Technical Book Division Frogmore, St. Albans, Berts, A 122NF, 10-24.
- Grisso, R.D., M.F. Kocher and M. Yasin, 1996. Tillage implement forces operating in silty clay loam. Transactions of the ASAE, 39 (6): 1977.
- Kaul, R.N. and C.O. Egbo, 1985. Introduction to Agricultural Mechanization. 1st Edn. Macmillan Publisher Ltd., London and Basingstoke, pp: 71-72.
- Manian, R., K. Kathirvel and V.R. Rao, 2000. Influence of Operating and Dics Parameters on Performance of Disks Tools. Agricultural Mechanization in Asia, Afr. Latin Am., 31: 19-22.
- Murray, R.S. and J.S. Larry, 2003. Statistics. 3rd Edn. Schaum's Outline Series. Mc Graw Hill Book Company, Singapore, pp: 311 -344.
- Olatunji, O.M. 2007. Modeling the Effect of Weight, Draught and Speed on the Depth of Cut of Disc Plough During Ploughing. M. tech Thesis, Department of Agricultural and Environmental Engineering. Rivers State University of Science and Technology. Port Harcourt, Nigeria. 102.
- RNAM. 1983. Test Codes and Procedures for Farm Machinery. Test Codes and Procedure for Ploughs. Regional Network for Agricultural Machines, Technical Series No. 12, Philippines. 4-21.
- Sheruddin, B.B., M.B. Jan and B.B. Allah, 1992. Performance of Selected Tillage Implements. Agricultural Mechanization in Asia. Afr. Latin Am., 19: 9-14.
- Sheruddin, B., R.M. Ghulam, Md. Zafarullah, Jan Baloch and Saleh Fanhwar. 1992. Effects of Disc and Tilt Angle on Field Capacity and Power Requirements of Mounted Plough. Agricultural Mechanization in Asia. Afr. Latin Am., 23:9-14.
- Singh, G. and T.T. Pedersen, 1979. Effect of Speed on Specific Draft of Mouldboard and Disc Ploughs in Bangkok clay. Agricultural Mechanization in Asia, Afr. Latin Am., 10: 30-35.
- Summers, J.D., A. Khalilan, and D.G. Batchelder, 1986. Draught Relationship for Primary Tillage in Oklahoma Soils. Transactions of the ASAE., 29: 37-39.
- Thomas, E.V. and B. Singh 2002. Performance of Tractor Implement Combination. Agricultural Mechanization in Asia. Afr. Latin Am., 33: 25-35.